

MOBILE

MPD31D Printer

The MPD31D is a light weight mobile printer with best in-class performance and economical price. It can be used in manufactory, warehouse, logistics, retail, public utilities and healthcare, healthcare.

Overview



Feedback

MPD31D is a 3 inch unit which can support one 1D, QR code, image, curves printing. It can also work with smart terminal devices like mobility as total solution.

MPD31D can support both receipt and label printing. Compatible with black mark paper, gap label, successive paper, seam paper, Sewing paper, continuous paper, lineless paper.

The MPD31D are fast mobile label printers for use in the most rugged environments. They feature the latest wireless technology for easy, untethered use, increasing worker productivity.

Specifications

FEATURES

Compatible Drivers

- Driver for Linux
- Windows

DIMENSIONS

Overall Dimensions

- H x W x D: 105 mm x 108 mm x 51 mm
(4.1 in x 4.3 in x 2.0 in)

SOFTWARE & FIRMWARE

Downloadable Font Type <ul style="list-style-type: none">• Bitmap Font• TrueType Font	Linear Barcodes <ul style="list-style-type: none">• All major 1D barcodes	2D Barcodes <ul style="list-style-type: none">• All major 2D barcodes
Printer Command Language <ul style="list-style-type: none">• CPCL• ESC/P• ESC/POS• XSIM• ZPL	Image File Format <ul style="list-style-type: none">• BMP• Bitmap	

PRINTING SPECIFICATIONS

Print Speeds <ul style="list-style-type: none">• 25-90 mm/s (1-3.5 ips)	Resolutions <ul style="list-style-type: none">• 203 dpi	Print Method <ul style="list-style-type: none">• Direct Thermal
--	--	--

MEDIA

Printer Media Type <ul style="list-style-type: none">• Label• Receipt	Maximum Media Roll Diameter <ul style="list-style-type: none">• 43 mm (1.69 in)
---	--

HARDWARE

Printer Connection Interface <ul style="list-style-type: none">• Micro USB

ELECTRICAL

Battery Capacity Options <ul style="list-style-type: none">• 2100 mAh	Operating Voltage <ul style="list-style-type: none">• 100 to 240 VAC
--	---

ENVIRONMENTAL

Operating Humidity <ul style="list-style-type: none">• 10% - 90 % non-condensing	Storage Humidity <ul style="list-style-type: none">• 10 - 90 % non-condensing
---	--

STANDARDS & APPROVALS

Drop Specifications <ul style="list-style-type: none">• 1.5 m (4.9 ft)	Protection Ratings <ul style="list-style-type: none">• IP54
---	--

Feedback

NETWORK

Bluetooth Specifications

- Bluetooth 4.0 + BLE

OTHERS

Application

- Healthcare
- Manufacturing
- Retail
- T&L

Weight range

- 0.4 kg (0.9 lb) (with battery, no media) keg

Operating Temperature

- -10°C to 50°C (14°F to 122°F)

Storage Temperature

- '-20°C to +70°C (-4°F to 158°F)

Warranty Duration

- One year factory warranty

Product Number

SKUs

SKU	DESCRIPTION
MPD31D-B	Carrying bag for 3" mobile printer
MPD31D-C	Belt clip for 3" mobile printer
MPD31D-R	Rubber Boot for MPD31D
MPD31D-S	Shoulder strap for 3" mobile printer
MPD31D111	3" MOBILE PRINTER, EU AC
MPD31D112	3" MOBILE PRINTER, US AC
MPD31D113	MPD31D,3" MOBILE PRINTER, INIDA AC
MPD31D114	3" MOBILE PRINTER, for UK
MPD31D115	3MOBILE PRINTER,ANZ AC
MPD31D116	3" MOBILE PRINTER, US AC, FOR BIMBO

Feedback

Honeywell
Safety and Productivity
Solutions
855 S Mint St
Charlotte, NC 28202
800-582-4263

MPD31D Printer
© 2023 Honeywell International Inc.
All rights reserved.



This document was generated on 2023-09-27 11:01:22 (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.